

Mains Pressure Small Storage Electric Water Heaters

PRODUCT FEATURES

- > Point of use installation - no need to install a larger remote system
- > Space-saving under bench installation
- > Main pressure tanks can service multiple outlets
- > Suitable for use with all standard taps (no specialty taps required)
- > Enamelled steel tank
- > Includes PTR valve
- > Temperature set at 75°C
- > Operates on 230V, plugs into standard power point
- > Safe tray and drain required as per AS/NZS 3500.4.2 & local regulations



SPECIFICATIONS

Item	6L Pressure	10L Pressure	15L Pressure
Product No.	2850003	2850004	2850005
Type	Pressure Storage	Pressure Storage	Pressure Storage
Capacity, L	6	10	15
Voltage, V	220 – 240Vac, 1-phase	220 – 240Vac, 1-phase	220 – 240Vac, 1-phase
Rated Power, W	2000	2000	2000
Rated Current, A	8.1 – 9.2	8.1 – 9.2	8.1 – 9.2
Temperature Setting, °C	75	75	75
Heating Time, mins. (ΔT = 30°C)	6.6	10.6	14.9
Max. Water Inlet Pressure, kPa	550	550	550
Min. Inlet Water Pressure, kPa	110	110	110
Max. Permissible Pressure, kPa	850	850	850
Weight, kg	6.2	7.4	8.4
Dimension, W x H x D mm	290 x 290 x 290	360 x 350 x 300	360 x 350 x 320
IP Rating	IPX4	IPX4	IPX4
Water Connections	Cold = G1/2" Male Hot = G1/2" Male	Cold = G1/2" Male Hot = G1/2" Male	Cold = G1/2" Male Hot = G1/2" Male
Tank Material	Steel	Steel	Steel
WaterMark Approval	WM 40394 (AS 3498)	WM 40394 (AS 3498)	WM 40394 (AS 3498)
Warranty	2 Years	2 Years	2 Years

