

Open Vented Small Storage Electric Water Heaters

PRODUCT FEATURES

- > Designed for point of use installation
no need to install a larger remote system
- > Space-saving under bench installation
- > Vented design to supply a single isolated outlet, no long piping requirements
- > Must be used with a vented tap
- > Enamelled steel tank
- > Includes PTR valve
- > Temperature set at 75°C
- > Operates on 230V, plugs into standard power point
- > Available in 6L and 10L capacities



SPECIFICATIONS

Item	6L Open Vented	10L Open Vented
Product No.	2850006	2850007
Type	Vented Storage	Vented Storage
Capacity, L	6	12
Voltage, V	220 – 240Vac, 1-phase	220 – 240Vac, 1-phase
Rated Power, W	2000	2000
Rated Current, A	8.1 – 9.2	8.1 – 9.2
Temperature Setting, °C	75	75
Heating Time, mins. (ΔT = 30°C)	6.6	10.6
Max. Water Inlet Pressure, kPa	550	550
Min. Inlet Water Pressure, kPa	110	110
Max. Permissible Pressure, kPa	850	850
Weight, kg	6.2	7.4
Dimension, W x H x D mm	290 x 290 x 290	360 x 350 x 300
IP Rating	IPX4	IPX4
Water Connections	Cold = G1/2" Male Hot = G1/2" Male	Cold = G1/2" Male Hot = G1/2" Male
Tank Material	Steel	Steel
WaterMark Approval	WM 40394 (AS 3498)	WM 40394 (AS 3498)
Warranty	2 Years	2 Years

